



LUPUSNET HD - LE910

Art. 100142

- 1/3" (8,5mm) CCD Chip, 752x576 Pixel (D1)
- Wide Dynamic Range (WDR)
- New 3D-DNR (noise reduction)
- Powerful H.264-compression
- 3GPP Live-Streaming to mobile phones
- Day/ night vision with IR-cut filter
- 0,00001 Lux @ F1.5 (SensUp)
- FTP-Upload also suitable for web streaming

MAIN FEATURES

The new LUPUSNET HD - LE 910 is the allrounder in our new LUPUSNET HD-Series. Its fantastic equipment combined with its very reasonable pricing and very easy installation makes this camera a reliable ally for every requirement. The 1/3" (8,5mm) CCD chip with 752x576 Pixel D1-resolution and technologies such as Wide Dynamic Range, SensUp and the new 3D-DNR noise reduction provide for fantastic image quality even in bad lighting conditions. And its powerful H.264 compression capabilities, Ethernet connection, 3GPP Streaming and many more allow for an outstanding communication performance in every network.

HARDWARE

CPU	ARM, 9, 32 bit RISC
RAM	256MB
Flash	16MB
Sensor	1/3" (8,5mm) CCD Sensor
Sensitivity	0.00001 lux @F1.5
Supports DC IRIS	Yes
I/O	1 Relay In- /1 Relay output
Lens	C/CS compatible lens (nicht im Lieferumfang)
ICR	IR cut filter
LED	N/A
IR Distance	N/A
RS-485	Yes
Video Out	1
Audio In	microphone builtin
Audio Out	1 (RCA Typ)
Power over Ethernet	Optional
Power consumption	DC 12V 450 mA
Operating temperature	0°C ~60°C
Dimensions	58mm (W) x 65mm (H) x 131.5mm (D)

NETWORK

Ethernet	10/100 Base-T
Network protocols	HTTP, TCP/ IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP
Wireless	-
Security	-

SYSTEM

Fullscreen	Yes
Privacy Mask	Yes, 3 different areas
Compression format	H.264/ MJPEG/ MPEG4 (3GPP only)
Video Bitrates Adjustment	CBR, VBR
Movement detection	Yes, 3 different areas
actionable items	Mail, FTP, save to SD-Card, relay out
Pre- / Postalarm	Yes, adjustable
Security	Password protected
Firmware Upgrade	HTTP Modus, via remote control
Multi user access	Yes, up to 10 parallel user
Audio	Yes, 2-Way
SD-Card recording	Movement detection, check IP, network crash (Ethernet only), schedule, relay out
SD-Video Format	AVI, JPEG
View record	Yes
Daten löschen	Ja

SYSTEM REQUIREMENTS

Operating system	Windows 2000, XP, 2003, Microsoft IE 6.0 or higher
Hardware recommended	Intel Dual Core 1.66G, RAM: 1024MB, graphics card: 128MB
Hardware minimum	Intel-C 2,8G, RAM:512MB, graphics card: 64MB

SCOPE OF DELIVERY

LupusnetHD Network Camera Model	LE910
Mount	included
Power adapter	12V 1A
Software	LupusnetHD Lite
User Manual	Quick User Manual for Camera, User Manual for Software and Camera on CD

Your LUPUS Certified Partner:

